

Jeep
APPLICATIONS



FULL THROTTLE BATTERY



**PREMIUM
AGM
BATTERIES**



Full Throttle: Cranking, Dual-Service, Hassle-Free

Full Throttle is a true dual-service battery equipped to handle the challenges presented in the backcountry. The TPPL (thin-plate, pure lead) grids provide a burst of energy on demand in hot or cold climates with rapid recharge once the alternator is spinning. The grids are heavily tinned allowing for use in light-duty cycling such as winching, navigation, lighting, and air systems. High compression cells connected with OTP (Over-The-Partition) technology ensure resilience when the road gets bumpy. The hassle-free, zero-spill technology allows for creative mounting, with no corrosion or dangerous gassing.



NON-HAZARDOUS



TPPL TECHNOLOGY



LONG LIFE



HIGH CRANKING



CORROSION-FREE



WEATHER RESISTANT

A Size To Fit All Your Needs

Full Throttle batteries come in a wide variety of sizes from 8Ah/100CCA to 225Ah/1450CCA, including 32 different automotive BCI sizes to fit thousands of vehicle makes and models.



FT825-34



FT680-48



FT825-78



FT850-94R



fullthrottlebattery.com

MORE THAN ENOUGH POWER TO FEED ALL OF YOUR JEEP'S ACCESSORIES

AUX LIGHTING



ON-BOARD GAS



NAVIGATION



WINCHES



Full Throttle Series AGM

FT MODEL	GROUP SIZE	CCA	PHCA	HCA	CA	CAP. C20 (AH)	RES. CAP. @ 25A (min)	POSITIVE TERM. POSITION	TERM. TYPE	DIMENSIONS (in / mm)				WEIGHT (lbs / kg)
										LENGTH	WIDTH	HEIGHT	TTL HEIGHT	
FT610-47	47/L2/H5	610	1280	890	745	50	105	RHP	AP	9.49 (241)	6.89 (175)	7.48 (190)	7.48 (190)	42.1 (19.1)
FT680-48	48/L3/H6	680	1320	975	810	60	120	RHP	AP	10.94 (278)	6.89 (175)	7.48 (190)	7.48 (190)	47.8 (21.7)
FT825-24	24	825	1500	1200	1000	65	135	LHP	M8 + TP28	10.28 (261)	6.77 (172)	8.19 (208)	8.90 (226)**	46.0 (20.9)
FT825-34	34	825	1500	1200	1000	65	135	LHP	SAE AP**	10.28 (261)	6.77 (172)	7.19 (182)	8.19 (208)**	46.0 (20.9)
FT825-78	34/78	825	1500	1200	1000	65	135	LHP	M8 + FR45	10.28 (261)	6.77 (172)	7.19 (182)	8.31 (211)	46.0 (20.9)
FT850-94R	94R/L4/H7	850	1888	1200	1070	85	175	RHP	AP	12.36 (314)	6.85 (174)	7.47 (190)	7.47 (190)	55.7 (25.3)
FT890-49	49/L5/H8	890	1800	1300	1070	80	168	RHP	AP	13.90 (353)	6.89 (175)	7.24 (184)	7.48 (190)	60.4 (27.4)
FT930-65	65	930	1750	1350	1070	75	142	LHP	M8 + TP28	11.81 (300)	7.17 (182)	6.65 (169)	7.24 (184)**	54.9 (24.5)

** Brass SAE post is removable reducing total height by 0.86" to 1.00"

Don't See Your Vehicle?



Use the "Battery Finder" feature on our website to find the perfect power solution for your vehicle.

"Full Throttle Battery. The one that works."



LONG LIFESPAN

Full Throttle AGM batteries last longer than their wet cell counterparts due to 99.994% pure virgin lead, high compression cells, and no maintenance needed.



FAST CHARGING

Full Throttle AGM incorporates very low internal resistance allowing for charge rates up to 35% of total amperage for faster charging.



BUILT STRONGER

Full Throttle AGM is built with TPPL (Thin Plate Pure Lead) technology and Over-The-Partition welds which greatly increase resistance to vibration and shock. The ABS case and optional metal jackets provide high heat resistance for the most abusive environments.



OUTSTANDING WARRANTY

Full Throttle AGM batteries are backed with a 4-year Full Replacement warranty on automotive group sizes for more time on the road, off the road, in the lanes, on the water, or anywhere.



FLEXIBLE INSTALLATION

AGM batteries can be mounted vertically or horizontally, allowing them to fit places traditional wet cell batteries cannot. Fullriver AGM incorporates recombinant technology for long life, and no off-gassing like traditional wet cell batteries. Install them inside without the worry of dangerous explosive and corrosive gases. No more corroded terminals or cables.



CONTACT US TODAY

800.522.8191