



DC224-6
GROUP GC2

PREMIUM DEEP CYCLE AGM BATTERIES

fullriverbattery.com

Why Choose a Fullriver Premium AGM Battery?

When it comes to marine applications, picking a battery solution can be tricky. Luckily, Fullriver produces batteries for all solutions. Our DC Series batteries are composed of thick plates that allow users to access more energy from the battery than a conventional flooded battery. Whether you're running the house lighting, fridge, bilge pump, running trolling motors and a fish finder on the lake, you won't have to worry about any power issues with a DC Series battery setup.

On the other hand, our Full Throttle Series is a true dual service battery, built to stand up to the challenges of recreational marine life. Hot or cold engine starts are not a problem for the TPPL grids which provide a huge burst of cranking on demand in almost any condition, all the while recharging quickly due to low internal resistance. If you're getting ready for a long day out on the water, Fullriver Battery will get you get started.



BUILT BETTER.

- ABS plastic is more rigid than PPE; does not bulge under normal operation.
- Rigid casing - Epoxy sealed case increases PSI limits
- Pure lead allows for more efficient transfer of electricity during discharge and recharge; less energy lost to heat.
- Over partition welding (OPW) provides greater shock and vibration resistance

Specifications on back →

Full Throttle FT Series Premium High Cranking AGM Batteries

FT MODEL	GROUP SIZE	CCA	PHCA	HCA	CA	CAP. C20 [AH]	RES. CAP. @ 25A [min]	POSITIVE TERM. POSITION	TERMINAL TYPE	DIMENSIONS (in/mm)				WEIGHT [lbs/kg]
										LENGTH	WIDTH	HEIGHT	TTL HEIGHT	
FT965-27	27	965	1950	1380	1170	100	185	LHP	DT	12.09 (307)	6.65 (169)	8.43 (214)	9.33 (237)	69.7 (31.6)
FT825-34	34	825	1500	1200	1000	65	135	LHP	M8 + TP28	10.28 (261)	6.77 (172)	7.19 (182)	8.19 (208)**	46.1 (20.9)
FT825-78	34/78	825	1500	1200	1000	65	135	LHP	SAE AP**	10.28 (261)	6.77 (172)	7.19 (182)	8.31 (211)	46.5 (21.1)
FT1100-31	31A	1100	2200	1560	1360	110	230	RHP	M8 + TP28	12.99 (330)	6.81 (173)	8.31 (211)	9.33 (237)**	75.2 (34.1)
FT1150-6T	6TL	1150	2250	1700	1450	120	273	RHP	M8 + TP28	11.02 (280)	10.43 (265)	8.11 (206)	8.85 (225)**	85.3 (38.7)
FT1250-4DLT	4DLT/D5	1250	2200	1720	1500	175	340	LHP	M8 + TP28	20.19 (513)	8.78 (223)	7.75 (197)	8.74 (222)**	124.3 (56.4)
FT1450-8D	8D	1450	2400	1950	1700	225	450	RHP	M8 + TP28	20.35 (517)	10.79 (274)	8.58 (218)	9.57 (243)**	161.4 (73.2)

Fullriver DC Series Premium Deep Cycle AGM Batteries

DC MODEL	VOLTS	GROUP SIZE	RES. CAPACITY [min]		CYC. CAPACITY [AH]		CRANKING [Amps]		TERMINAL TYPE	DIMENSIONS (in/mm)			WEIGHT [lb/kg]
			@ 25 Amps	@ 75 Amps	@ 5hr Rate	@ 20hr Rate	CA @ 32°F	CCA @ 0°F		LENGTH	WIDTH	TTL HEIGHT	
DC1150-2	2	L16	2235	658	945	1150	5400	4500	M10	11.61(295)	7.05 (179)	16.18 (411)	127.0 (57.6)
DC224-6	6	GC2	441	113	179	224	1080	900	M8 + TP08	10.24 (260)	7.08 (180)	10.70 (272)**	68.6 (31.1)
DC400-6	6	903/L16	885	229	340	415	1800	1500	DT	11.61(295)	7.05 (179)	16.69 (424)	124.6 (56.5)
DC85-12	12	24	145	34	70	85	600	510	M8 + TP08	10.24 (260)	6.65 (169)	9.29 (236)**	56.0 (25.4)
DC105-12	12	27	175	43	86	105	820	680	M8 + TP08	12.08 (307)	6.65 (169)	9.29 (236)**	67.5 (30.6)
DC115-12	12	31	200	45	91	115	910	760	M8 + TP08	12.91 (328)	6.67 (172)	4.44 (241)**	73.2 (33.2)
DC210-12	12	4D	400	105	172	210	1425	1180	LT / APW	20.86 (530)	8.22 (209)	8.58 (218)	134.1 (60.8)
DC260-12	12	8D	578	145	214	260	1830	1525	LT / APW	20.51 (521)	10.59 (269)	8.81 (224)	173.3 (78.6)

** Brass SAE post is removable, reducing total height by 0.86"



AGM Perfected.

FULLRIVER BATTERIES ARE AVAILABLE THROUGH OUR
NATIONWIDE NETWORK OF AUTHORIZED DEALERS
AND INTERNATIONAL BRANCHES. FOR MORE INFO
VISIT OUR WEBSITE OR CALL US TOLL FREE AT
800-522-8191 / 805-484-7900 (LOCAL).

fullriverbattery.com

